

DRY ACID AL

TECHNICAL DATA SHEET

DESCRIPTION:

DRY ACID AL is a specially inhibited acid blend for the removal of salt and corrosion products from aluminum. Due to the unique composition of **DRY ACID AL**, there is less discoloration of the bar metal than with typical acids.

PROPERTIES:

Appearance:	White powder with a slight odor.
Specific Gravity:	0.87
pH (8 oz. / gallon):	0.8 – 1.0
pH (1oz. / gallon):	1.0 – 1.5
Solubility:	Appreciable
Foam:	Nil
Metal Safety:	Safe on aluminum alloys. Slight attack on ferrous alloys. No appreciable effect on stainless steel alloys.

APPLICATION:

DRY ACID AL is used at 4 to 12 oz. / gallon at 140°F. to 180°F.

When using **DRY ACID AL**, allow the aluminum to soak until scale, rust, etc. are dissolved or loosened. Rinse with water after use.

PRODUCT CAUTIONS:

Warning! May cause skin or eye irritation. May be harmful if swallowed. Wear safety eyewear and impermeable gloves. Contains sulfamic acid.

EMERGENCY FIRST AID:

EYES & SKIN: Immediately flush with large quantities of cool water continuously for at least 15 minutes. Call a physician. Remove contaminated clothing and shoes. Do not put contaminated clothing and shoes back on. Wash clothing and shoes thoroughly in soap and water; rinse repeatedly in clean water and dry before reuse.

INGESTION: Do not induce vomiting. Give water. Never give anything by mouth to an unconscious person. Call a physician.

If use is contemplated for purposes other than, or by methods different from those specifically recommended herein, please contact the manufacturer for advice.

FOR INDUSTRIAL USE ONLY – KEEP OUT OF THE REACH OF CHILDREN.



Madison Chemical Co., Inc.

Formulating Solutions for Excellence

3141 Clifty Drive, Madison, IN 47250 (812)273-6000 www.madchem.com

2-13-2018